



*Advanced Technology  
Synthetic Lubricants* 

www.completelubricants.com

**PRODUCT SERIES – ATP  
FULL SYNTHETIC – AIR TOOL LUBRICANTS**

Series ATP air tool lubricants are blended from several synthetic base stocks to form a synergistic blend of fluids in conjunction with, the Complete Lubricant's additive infusion system to provide outstanding performance and maximum protection for modern air tools. It removes deposits and sludge from air tools while protecting them from moisture and component wear.

Application: Pneumatic Tools  
Product Life: Exceptional

***Product Features & Benefits***

Outstanding Oxidation Stability	Energy Savings
Very High Viscosity Index	Carbon & Varnish Control
High Flash & Auto-Ignition Points	Reduced Maintenance Cost
Very Low Volatility	Reduced Downtime
Extremely High Film Strength	Excellent Materials Compatibility
Excellent Coolant Properties	Reduced Lubricant Consumption
Long Fluid Life Cycle	Excellent Rust & Corrosion Control

		Product Designation	
		ATP	
Viscosity	ISO Grade		22
	Index		127
	cSt @	100°F / 40°C	106.3 / 22.0
	cSt @	212°F / 100°C	41.4 / 4.6
Flash Point		°F / °C	315 / 157.2
Auto-Ignition		°F / °C	655 / 346.1
Pour Point		°F / °C	-20 / -28.9
Copper Corrosion, 24 Hr		1a	
Demulsibility, 30 Min @ 130°F		40/40/0	
Wear Tests			
Four ball weld point (Kg)		-	
Four ball scar Dia. (mm) *		-	

\* Test basis is 40Kg ball @ 1200 RPM for 1 hour @ 167°F